

## Kontrolni kabli / Control Cables

## FLEX-JZ/OZ

Fleksibilni oštevilčeni kabli po standardu VDE 0250  
Flexible control cable, number coded

**Uporaba:**

Uporablja se kot povezovalni kabel, kot merilni, kontrolni kabel pri izdelavi obdelovalnih strojev, Pri visoki stopnji varnosti kot energetski ali povezovalni kabli za meritve, kontrolo in napajanje v industrijski proizvodnji in strojništvu. Kabel je primeren za fiksno montažo ali prilagodljivo uporabo s prostim gibanjem brez prisilnega nateznega stresa v suhih in vlažnih prostorih, vendar ne na prostem.

Dobra odpornost na kemikalije, v veliki meri so kabli odporni na olje.

**Konstrukcija:**

- Finožični vodniki iz pramenov golih bakrenih žičk
- PVC belo oštevilčeni črni vodniki
- Finožičnost po VDE 0295, klasa 5
- Ozemljitveni vodnik: rumeno/zeleni
- PVC zunanji plašč, siv RAL 7001

**Tehnični podatki:**

Material vodnika	goli baker
Fleksibilnost	klasa 5 po DIN VDE 0295, ali IEC 60228
Izolacija vodnika	PVC
Identifikacija vodnika	po DIN VDE 0293 belo oštevilčeni črni vodniki
zavijost bakrenih žic	vodniki v plasteh
Izolacija zunanjega plašča	PVC
Barva kabla	siva, RAL 7001
Nazivna napetost [V]	300 / 500
Testna napetost [V]	2000
Upornost vodnika	DIN VDE 0295, ali IEC 60228
Izolacijska upornost	> 20 MΩ x km
Stromobestirbarkeit	DIN VDE (glej tehn. prilogo)
Najmanjši pregibni radij fiksna inštalacija [xd]	4 x d
Najmanjši pregibni radij / premikajoča inštalacija [xd]	15 x d
Delovna temperatura pri fiksni inštalaciji min/max [C]	-40°C bis +80
Delovna temperatura /premikajoča inštalacija min/mac [C]	-15°C bis +80
Temperatura vodnika max.	+70°C med delovanjem, +150°C pri kratk. stiku
Ognjevarnost	IEC 60332-1: ognjeodpornost in samougasljivost
Mednarodna norma	EN 50525-2-11

**Application:**

Used as connecting cable, as measuring, checking and control cable in machine tool manufacturing, plant engineering and on assembly lines and production lines to meet stringent safety requirements.

Suitable for fixed installation or flexible applications with unrestricted mobility without forced movement control and without exposure to tensile load. Installation in dry and moist rooms; outdoor installation not permitted. Good chemical resistance, largely oil resistant.

**Construction:**

- fine strands of bare copper conductor
- PVC core insulation black with continuous white figure imprint
- stranding acc. to VDE 0295 class 5
- earth conductor green/yellow in other layer
- PVC outer sheath grey, RAL 7001

**Technical Data:**

Conductor Material	Copper, bare
Conductor class	Class 5 according DIN VDE 0295, resp. IEC 60228
core insulation	PVC
core identification	According DIN VDE 0293 black cores with white numerals
stranding	Cores twisted in layers
outer sheath	PVC
sheath colour	Grey, RAL 7001
rated voltage [V]	300/500
testing voltage [V]	2000
conductor resistance	DIN VDE 0295, resp. IEC 60228
insulation resistance	> 20 MΩ x km
current carrying capacity	DIN VDE (see technical data)
min. bending radius fixed [xd]	4 x d
min. bending radius moved [xd]	15 x d
working temp fixed min/max [C]	-40°C up to +80
working temp moved min/mac [C]	-15°C up to +80
temp at conductor max.	+70°C in operation, +150°C in case of short-circuit
burning behaviour	IEC 60332-1: flame-retardant and self-extinguishing
Approvals	EN 50525-2-11

## Kabel / Cable

Koda art. Part No.	Število vodnikov x presek mm <sup>2</sup> no. of cores x cross section mm <sup>2</sup>	Zunanji presek Ø cca. mm outer Ø ca. mm	Teža bakra kg/100m copper weight kg/100m	Teža kg/100m weight kg/100m
10020050	2 x 0.50 OZ	4.70	1.00	3.30
10020075	2 x 0.75 OZ	5.20	1.50	4.30
10020100	2 x 1 OZ	5.50	1.92	5.00
10020150	2 x 1.50 OZ	6.30	2.90	6.70
10020250	2 x 2.50 OZ	7.60	4.80	10.10
10020400	2 x 4 OZ	9.90	7.70	18.50
10030050	3 x 0.50	5.10	1.50	4.70
10030075	3 x 0.75	5.80	2.20	6.60
99030075	3 x 0.75 OZ	5.80	2.20	6.60
10030100	3 x 1	6.20	2.90	6.80
99030100	3 x 1 OZ	6.20	2.90	6.40
99030150	3 x 1.50 OZ	6.80	4.30	9.50
10030150	3 x 1.50	6.80	4.30	9.50
10030250	3 x 2.50	8.30	7.20	14.80
99030250	3 x 2.50 OZ	8.30	7.20	14.80
10030400	3 x 4	10.10	11.52	23.50
10030600	3 x 6	11.70	17.30	41.50
10031000	3 x 10	14.70	28.80	68.20
10031600	3 x 16	20.00	46.10	82.70
10033500	3 x 35	25.90	100.80	158.50
10035000	3 x 50	31.50	144.00	255.00
10040050	4 x 0.50	5.50	1.92	5.80
10040075	4 x 0.75	6.35	2.90	7.80
99040075	4 x 0.75 OZ	6.30	2.90	7.80
10040100	4 x 1	6.70	3.80	8.50
99040100	4 x 1 OZ	6.70	3.80	8.50
10040150	4 x 1.50	7.40	5.80	11.70
99040150	4 x 1.50 OZ	7.40	5.80	11.70
99040250	4 x 2.50 OZ	9.10	9.60	23.60
10040250	4 x 2.50	9.10	9.60	23.60
10040400	4 x 4	11.00	15.40	29.90
10040600	4 x 6	12.80	23.00	48.00
10041000	4 x 10	16.30	38.40	73.70
10041000	4 x 16	20.60	61.40	108.70
10042500	4 x 25	25.70	96.00	158.20
10043500	4 x 35	27.20	134.40	210.60

Koda art. Part No.	Število vodnikov x presek mm <sup>2</sup> no. of cores x cross section mm <sup>2</sup>	Zunanji presek Ø cca. mm outer Ø ca. mm	Teža bakra kg/100m copper weight kg/100m	Teža kg/100m weight kg/100m
10045000	4 x 50	36.70	192.00	296.30
10050050	5 x 0.50	6.20	2.40	7.50
99050050	5 x 0.50 OZ	6.20	2.40	7.50
10050075	5 x 0.75	6.90	3.60	9.10
99050075	5 x 0.75 OZ	6.90	3.60	9.10
99050100	5 x 1 OZ	7.30	4.80	11.00
10050100	5 x 1	7.30	4.80	11.00
99050150	5 x 1.50 OZ	7.40	7.20	15.20
10050150	5 x 1.50	7.40	7.20	15.20
10050250	5 x 2.50	10.20	12.00	26.30
99050250	5 x 2.50 OZ	10.20	12.00	26.30
10050400	5 x 4	12.00	19.20	36.30
10050600	5 x 6	14.40	28.80	58.30
10051000	5 x 10	18.20	48.00	91.40
10051600	5 x 16	22.40	76.80	137.00
10052500	5 x 25	28.70	120.00	199.80
10053500	5 x 35	34.70	168.00	248.50
10055000	5 x 50	37.00	240.00	393.60
10060050	6 x 0.50	6.90	2.90	7.50
10060075	6 x 0.75	7.50	4.32	10.80
99060075	6 x 0.75 OZ	7.50	4.32	10.80
10060100	6 x 1	8.10	5.80	13.50
10060150	6 x 1.50	8.50	8.60	18.30
10070050	7 x 0.50	6.80	3.40	9.30
99070050	7 x 0.50 OZ	6.80	3.40	9.30
10070075	7 x 0.75	7.50	5.00	12.40
99070075	7 x 0.75 OZ	7.50	5.00	12.40
99070100	7 x 1 OZ	8.70	6.70	14.60
10070100	7 x 1	8.70	6.70	14.60
99070150	7 x 1.50 OZ	8.90	10.10	19.20
10070150	7 x 1.50	8.90	10.10	19.20
10070250	7 x 2.50	11.25	16.80	29.80
99070250	7 x 2.50 OZ	11.30	16.80	29.80
10070400	7 x 4	13.60	26.90	48.80
10070600	7 x 6	16.00	40.30	78.20
10071000	7 x 10	20.10	67.20	119.10

## Kabel / Cable

Koda art. Part No.	Število vodnikov x presek mm <sup>2</sup> no. of cores x cross section mm <sup>2</sup>	Zunanji presek Ø cca. mm outer Ø ca. mm	Teža bakra kg/100m copper weight kg/100m	Teža kg/100m weight kg/100m
10071600	7 x 16	25.60	107.50	177.90
10072500	7 x 25	34.00	168.00	247.70
10080050	8 x 0.50	7.90	3.80	11.50
99080050	8 x 0.50 OZ	7.90	3.80	11.50
99080075	8 x 0.75 OZ	9.00	5.80	14.30
10080075	8 x 0.75	9.00	5.80	14.30
10080100	8 x 1	9.70	7.70	14.80
10080150	8 x 1.50	10.90	11.50	20.50
10080250	8 x 2.50	13.20	19.20	33.90
10090075	9 x 0.75	9.80	6.50	16.20
10090100	9 x 1	10.40	8.60	18.20
10090150	9 x 1.50	11.40	13.00	24.20
10100050	10 x 0.50	8.60	4.80	14.20
10100075	10 x 0.75	9.75	7.20	18.50
10100100	10 x 1	10.50	9.60	21.00
99100100	10 x 1 OZ	10.50	9.60	21.00
10100150	10 x 1.50	11.80	14.40	25.20
10100250	10 x 2.50	14.60	24.00	37.50
10110150	11 x 1.50	13.30	15.84	29.50
99120050	12 x 0.50 OZ	9.40	5.80	15.00
10120050	12 x 0.50	9.40	5.80	15.00
10120075	12 x 0.75	10.10	8.60	19.10
99120075	12 x 0.75 OZ	10.10	8.60	19.10
10120100	12 x 1	10.60	11.50	23.20
10120150	12 x 1.50	11.10	17.30	31.20
99120150	12 x 1.50 OZ	11.10	17.30	31.20
10120250	12 x 2.50	15.00	28.80	52.20
10120400	12 x 4	19.60	46.10	79.00
10140050	14 x 0.50	10.20	6.70	17.20
10140075	14 x 0.75	11.00	10.08	19.50
10140100	14 x 1	11.50	13.40	27.10
10140150	14 x 1.50	12.90	20.20	34.90
10140250	14 x 2.50	16.10	33.60	58.80
10150075	15 x 0.75	11.20	10.80	22.90
10160050	16 x 0.50	10.50	7.60	17.50
10160100	16 x 1	12.00	15.40	30.00

Koda art. Part No.	Število vodnikov x presek mm <sup>2</sup> no. of cores x cross section mm <sup>2</sup>	Zunanji presek Ø cca. mm outer Ø ca. mm	Teža bakra kg/100m copper weight kg/100m	Teža kg/100m weight kg/100m
10160150	16 x 1.50	13.70	23.00	40.30
10160250	16 x 2.50	18.40	38.40	66.50
10180050	18 x 0.50	11.50	8.60	21.60
10180075	18 x 0.75	12.00	13.00	28.30
10180100	18 x 1	13.00	17.30	32.80
99180100	18 x 1 OZ	13.00	17.30	32.80
10180150	18 x 1.50	14.65	25.90	45.60
10180250	18 x 2.50	18.10	43.20	74.90
10190100	19 x 1	13.90	18.30	34.60
10200075	20 x 0.75	14.26	14.40	32.00
10200100	20 x 1	13.70	19.20	35.70
99200100	20 x 1 OZ	13.70	19.20	35.70
10200150	20 x 1.50	16.40	28.80	50.70
10200250	20 x 2.50	20.80	48.00	83.20
10210050	21 x 0.50	12.80	10.10	24.90
10210075	21 x 0.75	13.30	15.10	29.30
10210100	21 x 1	14.40	20.20	44.40
10210150	21 x 1.50	16.40	30.20	57.30
10210250	21 x 2.50	21.90	50.40	92.80
10250050	25 x 0.50	13.30	12.00	25.70
10250075	25 x 0.75	14.00	18.00	38.80
10250100	25 x 1	14.90	24.00	53.10
10250150	25 x 1.50	17.20	36.00	63.80
10250250	25 x 2.50	21.10	60.00	102.40
10300050	30 x 0.50	14.40	14.40	31.20
10320075	32 x 0.75	15.50	23.00	54.10
10320150	32 x 1.50	20.82	46.10	82.00
10340050	34 x 0.50	15.75	16.30	39.80
10340075	34 x 0.75	16.20	24.50	44.80
10340100	34 x 1	17.50	32.60	54.90
10340150	34 x 1.50	19.70	49.00	72.80
10340250	34 x 2.50	24.70	81.60	115.00
10400050	40 x 0.50	17.10	19.20	45.10
10400250	40 x 2.50	29.20	96.00	149.90
10410075	41 x 0.75	17.90	29.60	53.30
10410100	41 x 1	19.10	39.40	66.80

## Kabel / Cable

Koda art. Part No.	Število vodnikov x presek mm <sup>2</sup> no. of cores x cross section mm <sup>2</sup>	Zunanji presek Ø cca. mm outer Ø ca. mm	Teža bakra kg/100m copper weight kg/100m	Teža kg/100m weight kg/100m
10420050	42 x 0.50	17.50	20.20	47.00
10420075	42 x 0.75	18.00	30.20	55.40
10420100	42 x 1	19.10	40.30	66.40
10420150	42 x 1.50	21.50	60.50	88.80
10420250	42 x 2.50	29.20	100.80	152.50
10500050	50 x 0.50	18.80	24.00	53.50
10500075	50 x 0.75	19.60	36.00	65.50
10500100	50 x 1	21.00	48.00	79.40
10500150	50 x 1.50	23.60	72.00	105.10
10500250	50 x 2.50	32.10	120.00	182.30
10520050	52 x 0.50	19.20	24.96	55.20
10560100	56 x 1	23.20	53.80	96.20
10610050	61 x 0.50	19.70	29.30	60.10
10610075	61 x 0.75	21.10	43.90	87.60
10610100	61 x 1	22.50	58.60	93.40
10610150	61 x 1.50	25.50	87.80	125.90
10610250	61 x 2.50	34.70	146.40	275.00
10650050	65 x 0.50	20.90	31.20	66.80
10650075	65 x 0.75	22.10	46.80	83.70
10650100	65 x 1	23.50	62.40	100.60
10650150	65 x 1.50	26.00	93.60	127.20
10800050	80 x 0.50	23.30	38.40	82.90
10800075	80 x 0.75	26.50	57.60	113.00
10800100	80 x 1	28.20	76.80	135.40
10800150	80 x 1.50	33.00	115.20	189.00
101000050	100 x 0.50	29.00	48.00	98.00
101000075	100 x 0.75	31.40	72.00	132.00
101000100	100 x 1	31.90	96.00	164.40
101000150	100 x 1.50	38.20	144.00	235.00
101000250	100 x 2.50	46.00	240.00	445.00